



Acoustical Surfaces, Inc.

SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION CONTROL SPECIALISTS

123 Columbia Court North • Suite 201 • Chaska, MN 55318

(952) 448-5300 • Fax (952) 448-2613 • (800) 448-0121



Email: sales@acousticalsurfaces.com

Visit our Website: www.acousticalsurfaces.com


We Identify and S.T.O.P. Your Noise Problem

HG Isolation Washer Bushing

Material:
Bridge Bearing
Neoprene



Acoustical Isolation



Bolt Isolation and
Seismic Relief
Application

Bolt and Rod Isolation Washer – Bushings are for isolation noise and serve as minimum isolation of vibration where mounts and hangers are not required. They are made up of high quality bridge-bearing neoprene for maximum performance and life.

HG WASHER DIMENSIONS (inches)

Type & Size	Bolt Dia.	H	T	HD	ID	OD
HG-25	1/4	3/8	1/8	1/2	1/4	1
HG-38	3/8	1/2	1/8	5/8	3/8	1 1/4
HG-50	1/2	1/2	1/8	3/4	1/2	1 5/8
HG-63	5/8	5/8	3/16	7/8	5/8	2
HG-75	3/4	5/8	3/16	1	3/4	2 1/4
HG-100	1	7/8	1/4	1 1/4	1	2 3/4
HG-125	1 1/4	7/8	1/4	1 1/2	1 1/4	3 1/4
HG-150	1 1/2	1	1/4	1 3/4	1 1/2	3 3/4

In seismic applications, HG's reduce bolt shearing impact forces which can occur in seismic areas. These shearing forces are responsible for significant equipment movement observed after recent California earthquakes.