



Acoustical Surfaces, Inc.

SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION CONTROL SPECIALISTS

123 Columbia Court North • Suite 201 • Chaska, MN 55318

(952) 448-5300 • Fax (952) 448-2613 • (800) 448-0121

Email: sales@acousticalsurfaces.com

Visit our Website: www.acousticalsurfaces.com

*We Identify and **S.T.O.P.** Your Noise Problems*

Solid Brass Handle Sets for SECURY Automatic Door Lock

Stock



01

Satin Chrome

Custom Order



03

Polished Brass

Custom Order



04

Antique Brass

Custom Order



05

Oil Rubbed Bronze

Custom Order



6

Black

Custom Order



11

Satin Nickel

Custom Order



25

Dark Bronze

Custom Order



28

Pewter





Acoustical Surfaces, Inc.

SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION CONTROL SPECIALISTS

123 Columbia Court North • Suite 201 • Chaska, MN 55318

(952) 448-5300 • Fax (952) 448-2613 • (800) 448-0121

Email: sales@acousticalsurfaces.com

Visit our Website: www.acousticalsurfaces.com

We Identify and S.T.O.P. Your Noise Problem

Simply Close the Door



The lock with the click
Automatic latchbolt projection
from 10 mm to 20 mm

THE SECURY AUTOMATIC DOOR LOCK

European technology in a North American Lock

By simply closing the door the upper and lower ¾" (20 mm) latches will instantly engage

By turning the key from outside or the knob from inside it will engage the 1" central deadbolt and block the top and bottom latches to become a **3-deadbolt locking system**

The Advantages

- 20 mm tempered steel latches engage behind the strike-plate and prevent the door from warping
- No lifting of the handle to engage locking points
- 90 degree thumbturn to engage deadbolt function
- The tapered latches always engage the keepers upon closing of the door
- The top and bottom locking points :
 - give more security
 - give better weather sealing performance
 - help reduce door warpage
- High grade 16 mm Stainless Steel faceplate for higher corrosion resistance
- Radiused ends on faceplate for a clean look and easy installation
- Available for standard and 8 foot doors, in 45, 50 and 60 mm backsets

** Can be fitted with Ferco handle trim sets*