



Acoustical Surfaces, Inc.

SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION CONTROL SPECIALISTS

123 Columbia Court North • Suite 201 • Chaska, MN 55318

(952) 448-5300 • Fax (952) 448-2613 • (800) 448-0121

Email: sales@acousticalsurfaces.com

Visit our Website: www.acousticalsurfaces.com

We Identify and S.T.O.P. Your Noise Problem

ACOUSTI-GASKET TAPE™

Acoustical Anti-Vibration Tape



- *Build Quieter Walls*
- *Reduces Foot Fault in Floor & Ceiling Construction*
- *Greatly Increases Floor, Ceiling and Wall STC & IIC*
- *Dissipates Sound Energy*
- *Peel & Stick Application*
- *Easy to Apply*
- *Reduces Vibration*
- *Reduces Noise Transfer*



Simply cover face of studs with peel & stick back Acousti-Gasket Tape.

HOW IT WORKS:

New technology uses a cellular membrane to dramatically reduce vibration transfer through hard surfaces. With it's peel and stick application, it's super easy to apply.

How does it reduce Sound Transmission and vibration transfer through common walls, floors and ceilings?

Acousti-Gasket Tape is of low density and viscoelastic cellular rubber, which means it is a poor transmitter or conductor of sound. *It will dissipate sound energy.*

Deflection: Pressure PSF	Average Deflection
100 lbs.	.027
200 lbs.	.046
500 lbs.	.090
1000 lbs.	.131
2000 lbs.	.174
4000 lbs.	.221

MATERIAL:

Made of an open cellular rubber reinforced with solid rubber particles bonded to cellulose with peel and stick back.

HOW TO APPLY:

Acousti-Gasket Tape is placed between floor joists and sub-floor sheathing *on studs or between* layers of drywall to greatly reduce sound and vibration transfer.

FEATURES:

Goes on quickly – 1200 sq ft area in about 30 minutes.

SIZE:

Roll size is 24' x 1-1/2".

THICKNESS:

5/16" thick (8mm).

APPLICATIONS:

- Perfect for noisy neighbors (common walls) ● Bathrooms ● Offices ● Classrooms ● Conference rooms ● Doctors offices ● Home theaters ● Laundry rooms ● Mechanical rooms ● Bedrooms ● Government/Law enforcement interrogation rooms ● Quiet rooms
- Sound recording studios ● Yacht/Boat engine rooms



Install without mess. Screw drywall to studs through Acousti-Gasket Tape.

**Under \$60.00 To Treat An
8' H x 11' W Common Wall!**