



Acoustical Surfaces, Inc.

SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION CONTROL SPECIALISTS

123 Columbia Court North • Suite 201 • Chaska, MN 55318

(952) 448-5300 • Fax (952) 448-2613 • (800) 448-0121

Email: sales@acousticalsurfaces.com

Visit our Website: www.acousticalsurfaces.com

We Identify and S.T.O.P. Your Noise Problems



Flat Faced Melamine Foam

Acoustical Melamine Foam

- **Class A Fire Retardant**
- **High Performance Sound Absorber**
- **Fiber Free**

MATERIAL: Open Cell Melamine Acoustical Foam

PATTERN: Flat

FEATURES: Designed For sound absorption in a wide range of frequencies. Increased surface absorption area

APPLICATIONS: Industrial, Commercial, Audio, OEM Residential Markets, Ceilings, Walls, Partitions, Sound/Recording Studios, Radio Stations, Board Rooms, Swimming Pools, Churches, Schools, Gun Ranges, Enclosures

THICKNESS: 1", 2"

SIZES: 2' x 2' & 2' x 4'

EDGE DETAIL: Square (also available with half-beveled edges by request)

DENSITY: 0.7lbs/cub. ft.

COLOR: *Standard:* Natural White or Light Grey

Latex or HPC Paint: Black, Light Grey, Almond

Painted: Black, Brown, Beige, Light Gray (Custom colors also available)

FLAMMABILITY: ASTM E84, Class A. Flame Spread: 6; Smoke Developed: 15

INSTALLATION: Acoustical Adhesive

Available as Hanging Acoustical Baffles

| ASI Flat Faced Melamine Foam Sound Absorption/Noise Reduction | | | | | | | |
|---|-------|-------|-------|------|------|------|------|
| | 125Hz | 250Hz | 500Hz | 1KHz | 2KHz | 4KHz | NRC |
| 1" | 0.10 | 0.10 | 0.30 | 0.70 | 0.80 | 0.90 | 0.60 |
| 2" | 0.10 | 0.35 | 0.90 | 1.25 | 1.15 | 1.10 | 1.00 |

