# **Chemical Product and Company Identification**

Description:	Green Glue constrained layer damping adhesive	
Product Type: Latex based damping adhesive		

Manufacturer/Supplier Information:	
MSDS Prepared by:	
Audio Alloy, LLC.	
2121 East Stewart Rd.	
Midland, MI 48640	

# **Emergency Phone Number: None Given**

For additional health, safety or regulatory information, to place an order, or request additional MSDS call 989-832-1602.

# 02. Composition, Information on Ingredients

Before using, Handing, or Exposure to these ingredients, read and understand the MSDS.

Name:	CAS number:	Percent by weight:
Alkana diol	Not available	<3%
Ammonia:	7664-41-7	0-0.5%
2-Amino-2-Methyl-1-Propanol	124-68-5	0-0.5%

# 03. Hazards Identification

Emergency Overview		
Appearance: thin, light green paste		
Odor:	Slight ammonia to no odor	
Fire Hazard	Not a Significant fire Hazard	

HMIS Rating	
Health: 1 (slight)	
Flammability: 0 (minimal)	
Chronic:	0 (minimal)

# 03.1 Potential Health Effects

Immediate Hazards		
Ingestion:	Potential irritant, do not ingest	
Inhalation	Not expected to be harmful under normal conditions of use. However, if allowed to become airborne, may cause irritation of nose, throat and lungs. Pail may have slight ammonia odor when opened after storage.	
Skin:	May cause irritation on prolonged or repeated contact, brief contact is not anticipated or shown to cause irritation.	
Eyes:	May cause irritation.	

# 03.2 Delayed Hazads

None known to company

#### 04.First Aid Measures

Immediate Hazard	ds
Ingestion:	If accidentally swallowed, dilute by drinking large quantities of water. Immediately contact poison control center or hospital emergency room for any other additional treatment directions.
Inhalation	Remove to fresh air.
Skin:	In case of contact, flush with water and wash until clean. If material is noticed on skin before dry, wash prior to material drying if at all possible.
Eyes:	Immediately flush eyes with plenty of water. Call a physician if irritation persists.

### 05. Fire Fighting Measures

Auto ignition Temperature:	Not available	
Upper/Lower Flammable Limits:	Not available	
Up/Lower Explosive Limits, % by Vol:	Not applicable	
Flash Point:	Not available	
Material is incombustible as supplied, but dried material will support combustion.  In case of fire, water should be used to keep fire-exposed containers cool.		

# 06. Accidental Release Measures

Soak up with absorbent material and remove to a chemical disposal area. Prevent entry into natural bodies of water.

### 07. Handling and Storage

07.1 Handling		
unnecessary exp	dance with good industrial hygiene and safety practices. These practices include avoiding posure and removal of the material from eyes, skin and clothing. Wash thoroughly after handling, opriate Personal Protective Equipment (PPE).	
Inhalation:	Avoid prolonged or repeated breathing of vapor.	
Skin:	Utilize gloves to avoid skin contact.	
Ingestion:	Do not intentionally ingest material.	

07.2 Storage	
Keeping from Freezing	
Store in a cool, dry place.	
Keep containers tightly closed	

### 08. Exposure Controls/Personal Protection

# 08.1 Exposure Controls

If airborne contaminants are generated when the material is heated or handled, ventilation should be provided to keep air contaminant concentration levels below applicable limits. Airborne material should not ever occur under normal handling.

#### 08.2 Personal Protection

Where air contaminants can exceed acceptable criteria, use NIOSH/MSHA approvedrespiratory protection equipment. Wear water-impervious gloves as required toprevent skin contact during all use. Latex gloves work nicely.

Page 2 of 4 - Green Glue MSDS

## 08.3 Exposure Guidelines

Airborne Exposure Limits	
For Ammonia:	
- OSHA Permissible Exposure Limit (PEL)	50 ppm (TWA)
- ACGIH Threshold Limit Value (TLV)	25 ppm (TWA), 35 ppm (STEL)

#### Toxicity Date:

Data is not available for toxicity or irritation. The low toxicity and non-reactive nature of the components used to make the product imply that the product probably has very low toxic potential. The product is not a listed carcinogen. This product should be used as recommended above, but only under extraordinary conditions would enough ammonia volatilize to approach the recommended levels.

### 09. Physical and Chemical Properties

oc. I my diedratie ettermedi i repetate		
Percent Volatiles:	25-40	
pH @ 25 C:	7-10	
Specific Gravity:	1.03-1.08	
Appearance:	Light green colored thin paste	
Autoignition Temperature:	Not applicable	
Boiling Point:	100 deg C	
Vapor Density (Air=1):	< 1	
Vapor Pressure:	mm Hg @ 20 C	
Evaporation Rate (Butyl Acetate=1):	< 1	
Upper/Lower Flammable Limits:	Not applicable	
Up/Lower Explosive Limits, % by Vol:	Not applicable	
Flash Point:	Not applicable	
Freezing Point:	0 deg C	
Odor:	Slight ammonia	
Odor Threshold, ppm:	Not applicable	
Solubility in Water:	Dispersible with stirring	

## 10. Stability and Reactivity

Stability & Reactivity:	Stable
Incompatibles:	Strong acids and alkaline materials (may cause gellation).
Decomposition Products may include:	CO, CO2
Hazardous Polymerization:	Will not occur.
Other Hazards:	None known

# 11. Toxicological Informations

Chronic/Carcinogenicity:	no
LD50:	Not available

#### 12. Ecological Information

Not Determined

#### 13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations.

Page 3 of 4 - Green Glue MSDS



# 14. Transport Information

Not Regulated

# 15. Regulatory Information (Selected Regulations)

15.1 U.S. Federal Regulations:	
Canadian Regulatory Information:	This product is not classified as hazardous under WHMIS.
VOC:	<5 gram per liter (calculated)

# TSCA Section 8(b) Inventory

All reportable chemical substances are listed on the TSCA Inventory or is governedby CFR (Code Federal Regulation) section 40 CFR 723.250, "Benign exemption", exempting it from mandate of TSCA registry. We rely on certifications of compliance from our suppliers.

### 16. Other Information

### **User's Responsibility**

The OSHA Hazard Communication Standard 29CFR 1910.1200 and the Workplace Hazardous Materials Information System (WHMIS) require that the information contained on these sheets be made available to your workers. Trained, educated workers are your companies greatest safety asset.

### Disclaimer

SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MER-CHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE, except that the product shall conform to contracted specifications, and that the product does not infringe any valid United States or Canadian patent. All claims shall be limited to purchase price only. Seller is liable in no event for incidental or consequential damages, whether Buyer's claim is based on contract, breach of warranty, negligence or otherwise. Seller certifies only that the information in this sheet is, to the limits of their knowledge, accurate. Seller relies to some extent on supplier data and is not responsible for errors contained therein.