



Acoustical Surfaces, Inc.

SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION CONTROL SPECIALISTS

123 Columbia Court North • Suite 201 • Chaska, MN 55318

(952) 448-5300 • Fax (952) 448-2613 • (800) 448-0121

Email: sales@acousticalsurfaces.com

Visit our Website: www.acousticalsurfaces.com

We Identify and S.T.O.P. Your Noise Problem

Smart Sound Level Sensors

smartSMS

SMS-S-100

The SmartSMS sound masking system is equipped with an adaptive adjustment system. The ambient noise in a zone is measured and the masking sound level is adjusted based on this measurement.

The Soft dB's SMS-S-100 Sound Level Sensor measures the ambient noise level in a zone. It is installed through a 9.5 mm (3/8") hole in acoustic tile. In the case of an open ceiling, it can be fixed to the structure.

Typically one sensor covers 1 000 sq ft and up to 8 sensors can be installed in one zone.

Features:

- Back electret type designed for high resistance to vibrations, high signal-to-noise ratio
- High sensitivity type

Specifications

Sensitivity:	-35±4 dB (0 dB = 1V/pa, 1 kHz)
Directivity:	Omnidirectional
Frequency range:	20-20,000 Hz
Diameter:	3/8 in.
Length:	2¾ in. approx.
Standard operation voltage:	3 volts
Current consumption:	Max. 0.5 mA
S/N ratio:	More than 62 dB
Measurement range:	35 to 95 dB at 17 mV/Pa
Connectors Type:	BNC



Specifications are subject to change without notice

Contact: Christian St-Pierre
(514) 727-3800
(514) 703-1553
c.stpierre@softdb.com

Soft dB