

# **Acoustical Surfaces, Inc.**

SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION CONTROL SPECIALISTS

123 Columbia Court North •Suite 201 •Chaska, MN 55318 (952) 448-5300 •Fax (952) 448-2613 •(800) 448-0121

Email: <a href="mailto:sales@acousticalsurfaces.com">sales@acousticalsurfaces.com</a>
Visit our Website: <a href="mailto:www.acousticalsurfaces.com">www.acousticalsurfaces.com</a>

# We Identify and S.T.O.P. Your Noise Problem

### **Surface-Mount Sound Masking Loudspeaker**

## smartSMS

### **SMS-SURF**

The Soft dB's SMS-SURF is a 25-volt system loudspeaker designed to generates the optimum masking sound for surface-mounted applications. It is equipped with a 16.5 cm (6.5 in.) driver installed in a sealed enclosure.

The SMS-SURF must be installed on the surface of drywall ceiling or on ceiling tiles through a 19.3 cm (8.6 in.) diameter hole. Four different power taps (½, 1, 2 and 4 W) controlled with a rotary switch allows quick adjustments of the output level. ROHS compliant.



### **Specifications**

Power:	10 watts
Line Voltage:	25 V
Sensitivity:	88 dB
Material:	ABS fire proof
Frequency Response:	100-8000 Hz

Connectors: Spring Loaded Terminals
Driver: 16.5 cm (6.5 in.) fullrange

Color: White
Weight: 1.8 kg (4 lbs)
Shipping Weight: 2 kg (4.4 lbs)


### **Dimensions**



### Frequency Response

# 80 /U | (Table of table of tab

### **Polar Response**



Specifications are subject to change without notice

Contact: Christian St-Pierre (514) 727-3800 (514) 703-1553 c.stpierre@softdb.com

