SILK METAL

Micro-Perforated Acoustical Ceiling & Wall Panels





FEATURES:

- Tegular Lay-in Tiles
- Flat Lay-in Tiles
- Anodized & Custom Printing Available
- Cost-Effective
- Installs into Standard 15/6" Grid
- Custom Wall Panels
- **■** Excellent NRC Rating
- Achieves .80 NRC (per ASTM C423) with a 4" Airspace, No Liner Needed

Silk Metal uses a patented angled micro-perforation method rather than traditional direct 90° punching methods. Silk Metal features an ideal surface to absorb wave energy generated by sound and electromagnetic waves, and for heat mitigation.

PRODUCT INFORMATION:

- Achieves acoustical value without acoustical liner
- Resembles smooth fabric surface in appearance
- Reversible surfaces
- Can be fabricated into various forms & sizes
- Tested as a "sheet good" to prove its electromagnetic wave attenuation characteristics
- The only surface material that has been tested to prove its AEMIC (acoustical & electromagnetic interference control) capabilities

APPLICATIONS:

- Restaurants Pro Audio/Recording Studios Home Theaters Ceilings
- Walls Hallways Public Spaces Swimming Pools Cafeterias
- Shopping Malls Offices Conference Rooms Classrooms Hospitals
- Lobbies Department Stores Exhibition Space Train Stations

· Airports · Concert Halls · Night Clubs · Practice Rooms

LAY-IN SYSTEM:

Appearance: Flat or Tegular

Stock Colors & Sizes: 23¾" x 23¾", White - 3/8" – Tegular Edge or 23¾" x 23¾", Black - 5/8" – Tegular Edge

MAXIMUM PANEL SIZE:

26¾" x 78¾"







Standard Lay-in for 15/16" Grid



ACOUSTICAL SURFACES, INC., 123 Columbia Court North ■ Chaska, MN 55318 952.448.5300 ■ 888.237.6425 ■ sales@acousticalsurfaces.com ■ www.acousticalsurfaces.com