

# Acoustical Surfaces, Inc. SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION CONTROL SPECIALISTS

123 Columbia Court North • Suite 201 • Chaska, MN 55318 (952) 448-5300 • Fax (952) 448-2613 • (800) 448-0121

Email: sales@acousticalsurfaces.com Visit our Website: www.acousticalsurfaces.com

#### We Identify and S.T.O.P. Your Noise Problems

#### MATERIAL SAFETY DATA SHEET

Page 1 or 4

| PRODUCT NAME:   | PVC COMPOSITE MATERIAL |                       |                                |  |                           |  |  |  |
|---|------------------------|-----------------------|--------------------------------|--|---------------------------|--|--|--|
| Rendered by Manufacturer a<br>123 Columbia Court No   |                        |                       | MN 55318                       | <b>PHONE NUMBER</b> N 55318 1-800-448-3134 |                           |  |  |  |
| CHEMICAL NAME AND SYNONYMS: FUSED PVC VINYLPlastisol COMPOSITE  |                        |                       |                                |  |                           |  |  |  |
| TRADE NAME AND SYNONYMS:  1.0 LB> / 1.5 LB./ft² – Loaded Solid Barrier, Solid Sound Barrier WITH VINYL FOAM COMPOSITE   |                        |                       |                                |  |                           |  |  |  |
| CHEMICAL FAMILY: Plasticized Polyvinylchloride Dispersion   |                        |                       | FORMULA:<br>(C2H3CI) x Mixture |  |                           |  |  |  |
| C.A.S. REGISTRY NUMBER:<br>See Next Section   |                        | ISSUE DAT<br>06/10/20 |                                |  | REVISION DATE:<br>10/9/99 |  |  |  |
| II. HAZARDOUS INGREDIENTS / COMPOSITION INFORMATION   |                        |                       |                                |  |                           |  |  |  |
| ITEM  | CAS                    | Number                | <u>%</u>                       | TLV  | <u>Hazard</u>             |  |  |  |
| This product contains no known hazardous ingredients as defined under the Hazardous Communication Program Standard, Section 1910.1200   |                        |                       |                                |  |                           |  |  |  |
| SARA Title III Information – See 'Regulatory Information' Section, Page 4 *See 'Additional Comments' Section, Page 4  |                        |                       |                                |  |                           |  |  |  |
| III. HEALTH HAZARD SUMMARY  |                        |                       |                                |  |                           |  |  |  |
| SIGNS AND SYMPTOMS OF EXPOSURE: This product contains 15-16% mixed phthalate esters. They have low toxicity. AOGIH and OSHA have not established specific exposure limits for these plasticizers, but chemically-similar plasticizers have OSHA/AOGIH exposure limits of 5 mg/m³, 8 hour time weighted average. |                        |                       |                                |  |                           |  |  |  |
| Subjecting the material to temperature above 250°F may liberate modest quantities of plasticizer (-2%). At temperatures above 400°F, the product may decompose to HCI, $CO_2$ , and other gases.  |                        |                       |                                |  |                           |  |  |  |
| PRIMARY ROUTES OF EXPOSURE:<br>Inhalation of Processing Vapors  |                        | EXPOSURE              | LIMITS:                        | TLV  |                           |  |  |  |
| TOXICOLOGICAL PROPERT   | IES:                   |                       |                                |  |                           |  |  |  |
| <ul> <li>PLASTICIZER PORTION ONLY –</li> <li>Upon exposure, these plasticizers represent a low hazard in the areas of inhalation, eyes, skin, and ingestion, for the usual industrial or commercial handing by trained personnel.</li> </ul>  |                        |                       |                                |  |                           |  |  |  |



## Acoustical Surfaces, Inc. SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION CONTROL SPECIALISTS

123 Columbia Court North • Suite 201 • Chaska, MN 55318 (952) 448-5300 • Fax (952) 448-2613 • (800) 448-0121

Email: <a href="mailto:sales@acousticalsurfaces.com">sales@acousticalsurfaces.com</a> Visit our Website: www.acousticalsurfaces.com

### We Identify and S.T.O.P. Your Noise Problems

| IV. EME   | IV. EMERGENCY AND FIRST AIR PROCEDURES |   |   |  |  |  |  |  |
|---|--|---|---|--|--|--|--|--|
| EYE CONTACT: Flush eyes for 15 minutes with plenty of water, Call a physician if irritation persists.   |  |   |   |  |  |  |  |  |
| SKIN CONTACT:<br>Wash with soap and water.  |  |   |   |  |  |  |  |  |
| INHALATION:<br>When heated to decomposition, p  | orovide ventilation o                  | r use a NIOSF   | H-approved respirator.                      |  |  |  |  |  |
| INGESTION:<br>N/A   |  |   |   |  |  |  |  |  |
| V. PHYSICAL DATA  |  |   |   |  |  |  |  |  |
| BOILING POINT:  |  | SPECIFIC GRAVITY (H <sub>2</sub> O = 1 g/cm <sup>3</sup> ):<br>2.14 g/cm <sup>3</sup> (solid at 0.090 in) |   |  |  |  |  |  |
| VAPOR PRESSURE:   |  | VAPOR DENSITY (AIR = 1):  |   |  |  |  |  |  |
| FREEZING POINT:   | FREEZING POINT:                        |   | MOLECULAR WT.:                              |  |  |  |  |  |
| VAPOR PRESSURE:   |  | VAPOR DENSITY (AIR = 1):  |   |  |  |  |  |  |
| SOLUBILITY IN WATER:<br>Not soluble   |  | APPEARANCE AND ODOR: Solid; Mild characteristic odor  |   |  |  |  |  |  |
| VI. F   | VI. FIRE AND EXPLOSION HAZARD DATA     |   |   |  |  |  |  |  |
| FLASH POINT (METHOD USED):<br>>400 F. COC   |  |   | FLAMMABLE LIMITS (% BY VOL):<br>LEL N/A UEL |  |  |  |  |  |
| EXTINGUISHING MEDIA: Fires involving this product can be extinguished by dry chemical, CO <sub>2</sub> , foam, or water. Use NIOSH-approved pressure demand self-contained breathing apparatus, due to possible liberation of HCI, CO, or other gasses. |  |   |   |  |  |  |  |  |
| UNUSUAL FIRE AND EXPLOSION HAZA<br>None Known   | ARDS:                                  |   |   |  |  |  |  |  |
|   | VII. REACTIVITY DATA                   |   |   |  |  |  |  |  |
| STABILITY: Unstable X Stable X  | CONDITIONS TO A<br>None                | CONDITIONS TO AVOID None  |   |  |  |  |  |  |
| INCOMPATIBILITY (Materials to Avoid): Not Reactive  |  |   |   |  |  |  |  |  |
| HAZARDOUS DECOMPOSITION PRODUCTS: Thermal Oxides of Carbon (CO, CO <sub>2</sub> ).  |  |   |   |  |  |  |  |  |
| HAZARDOUS POLYMERIZATION: Unstable Stable   | CONDITIONS TO A<br>None                | CONDITIONS TO AVOID None  |   |  |  |  |  |  |



# Acoustical Surfaces, Inc. SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION CONTROL SPECIALISTS

123 Columbia Court North • Suite 201 • Chaska, MN 55318 (952) 448-5300 • Fax (952) 448-2613 • (800) 448-0121

Email: sales@acousticalsurfaces.com Visit our Website: www.acousticalsurfaces.com

### We Identify and S.T.O.P. Your Noise Problems

| VIII. OCCUPATIONAL CONTROL PROCEDURES   |  |  |  |  |  |  |
|---|--|--|--|--|--|--|
| EYE PROTECTION:<br>N/A.   |  |  |  |  |  |  |
| SKIN PROTECTION:<br>N/A.  |  |  |  |  |  |  |
| RESPIRATORY PROTECTION: When heated to decomposition, provide ventilation or NIOSH-approved chemical cartridge respirator.  |  |  |  |  |  |  |
| OTHER PROTECTIVE EQUIPMENT:   |  |  |  |  |  |  |
| VENTILATION:  |  |  |  |  |  |  |
| IX. SPILL, LEAK OR DISPOSAL INFORMATION   |  |  |  |  |  |  |
| STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Re-roll, pick-up, sweep, shovel, or vacuum   |  |  |  |  |  |  |
| WASTE DISPOSAL METHOD: Waste vinyl is not a hazardous material as defined by the Resource Conservation and Recovery Act. This material is suitable for landfilling or component recovery. Vinyl material may be incinerated under conditions which control associated chlorine formation. |  |  |  |  |  |  |
| X. SPECIAL STORAGE / HANDLING REQUIREMENTS  |  |  |  |  |  |  |
| Store product below 120°F to minimize the volatilization of the plasticizer components. Follow good ergonomic principles when handling.   |  |  |  |  |  |  |
| XI. LABEL REQUIREMENTS  |  |  |  |  |  |  |
| N/A   |  |  |  |  |  |  |



### Acoustical Surfaces, Inc.

SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION CONTROL SPECIALISTS

123 Columbia Court North • Suite 201 • Chaska, MN 55318 (952) 448-5300 • Fax (952) 448-2613 • (800) 448-0121

Email: sales@acousticalsurfaces.com Visit our Website: www.acousticalsurfaces.com

### We Identify and S.T.O.P. Your Noise Problems

#### XII. REGULATORY INFORMATION

**ITEM** 


C.A.S. Number

<u>%</u>

This product contains no known SARA Title III, 313 reportable chemicals at or above de minis amounts.

CMA TRANSPORTATION EMERGENCY ASSISTANCE CHEMTREC (800) 424-9300

NPCA/HMIS RATING:



HAZARD RATING:

Severe

3 Serious


Moderate

Slight

Minimal

FLAMMABILITY

HAZARD



ADDITIONAL COMMENTS

PREPARED BY:

**REVIEWED BY:** 

Ron L. King Chemist/Safety Officer Ron L. King Chemist/Technical Director

"Information on this form is furnished solely or the purpose of compliance with the Occupational Safety and Health Act of 1970 and applicable regulations, and should not be used for any other purpose. No warranty, expressed or implied, of merchantability, fitness for purpose, or any other nature regarding this data or the product is made herein."

<sup>•</sup> Soundproofing Products • Sonex™ Ceiling & Wall Panels • Sound Control Curtains • Equipment Enclosures • Acoustical Baffles & Banners • Solid Wood & Veneer Acoustical Ceiling & Wall Systems • Professional Audio Acoustics • Vibration & Damping Control • Fire Retardant Acoustics • Hearing Protection • Moisture & Impact Resistant Products • Floor Impact Noise Reduction • Sound Absorbers • Noise Barriers • Fabric Wrapped Wall Panels • Acoustical Foam (Egg Crate) • Acoustical Sealants & Adhesives • Outdoor Noise Control • Assistive Listening Devices • OSHA, FDA, ADA Compliance • On-Site Acoustical Analysis • Acoustical Design & Consulting • Large Inventory • Fast Shipment • No Project too Large or Small • Major Credit Cards Accepted