



# Acoustical Surfaces, Inc.

**SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION CONTROL SPECIALISTS**

123 Columbia Court North • Suite 201 • Chaska, MN 55318

(952) 448-5300 • Fax (952) 448-2613 • (800) 448-0121

Email: [sales@acousticalsurfaces.com](mailto:sales@acousticalsurfaces.com)

Visit our Website: [www.acousticalsurfaces.com](http://www.acousticalsurfaces.com)

## We Identify and **S.T.O.P.** Your Noise Problem

### MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND DISTRIBUTOR'S INFORMATION					
NFPA Rating: Health-2; Flammability -3; Reactivity -0; Special- -		HMIS Rating: Health-2; Flammability -3; Reactivity -0; Personal Protection-B			
<b>Manufactured for:</b> Acoustical Surfaces, Inc. 123 Columbia Court North, Suite 201 Chaska, MN 55318 <b>Phone:</b> 1-800-448-0121		<b>DOT Hazard Classification:</b> ORM-D Identity (trade name as used on label): <b>ASI WIDE WEB SPRAY ADHESIVE</b> <b>MSDS Number:</b> A00315 Revision-11			
<b>Emergency Response Number:</b> 1-800-255-3924 NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA		Date Prepared: 10/28/05 Prepared By IB/TR Information Calls: (770) 422-2071			
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION					
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)	CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref. Source**
ACETONE	67-64-1	No	1000	750	d
HEXANE	142-82-5	No	500	400	d
ISOBUTANE / PROPANE BLEND	75-28-5	No	800	800	d
	74-98-6	No	1000	1000	d
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS					
Boiling Point: N/A		Specific Gravity (H <sub>2</sub> O=1): Concentrate Only = 0.853			
Vapor Pressure: PSIG @ 70°F (Aerosols): Max. 80		Vapor Pressure: (Non-Aerosols) (mm Hg and Temperature): N/A			
Vapor Density (Air = 1): N/E		Evaporation Rate ( = 1): N/E			
Solubility in Water: Partial		Water Reactive: No			
Appearance and Odor: Straw colored liquid with ketone solvent odor.					
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA					
FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols) <b>EXTREMELY FLAMMABLE</b>		Auto Ignition Temperature N/E		Flammability Limits in Air by % in Volume: % LEL: N/E % UEL: N/E	
FLASH POINT AND METHOD USED (non-aerosols): N/A		SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus. Use water fog to cool containers to prevent rupturing & exploding containers. Provide shielding for personnel.			
EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide, water.					
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.					
SECTION 4 - REACTIVITY HAZARD DATA					
STABILITY [X] STABLE [ ] UNSTABLE		HAZARDOUS POLYMERIZATION [ ] WILL [X] WILL NOT OCCUR			
Incompatibility (Mat. to avoid): Strong oxidizing agents.		Conditions to Avoid: Open flame, welding arcs, heat, sparks.			
Hazardous Decomposition Products: Carbon dioxide, carbon monoxide.					
SECTION 5 - HEALTH HAZARD DATA					
PRIMARY ROUTES OF ENTRY: [X] INHALATION [ ] INGESTION [X] SKIN ABSORPTION [ ] EYE [ ] NOT HAZARDOUS					
ACUTE EFFECTS					
Inhalation: Excessive inhalation of vapors can cause nasal & respiratory irritation, dizziness, weakness, nausea, headache, possible unconsciousness or asphyxiation.					
Eye Contact: Irritation.		Skin Contact: Irritation due to defatting of skin.			
Ingestion: Possible chemical pneumonitis if aspirated into lungs.					
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) Excessive inhalation of solvents may cause brain and nervous system damage.					
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.					

Continued on next page

- Soundproofing Products • Sonex™ Ceiling & Wall Panels • Sound Control Curtains • Equipment Enclosures • Acoustical Baffles & Banners • Solid Wood & Veneer Acoustical Ceiling & Wall Systems
- Professional Audio Acoustics • Vibration & Damping Control • Fire Retardant Acoustics • Hearing Protection • Moisture & Impact Resistant Products • Floor Impact Noise Reduction
- Sound Absorbers • Noise Barriers • Fabric Wrapped Wall Panels • Acoustical Foam (Egg Crate) • Acoustical Sealants & Adhesives • Outdoor Noise Control • Assistive Listening Devices
- OSHA, FDA, ADA Compliance • On-Site Acoustical Analysis • Acoustical Design & Consulting • Large Inventory • Fast Shipment • No Project too Large or Small • Major Credit Cards Accepted



# Acoustical Surfaces, Inc.

**SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION CONTROL SPECIALISTS**

123 Columbia Court North • Suite 201 • Chaska, MN 55318  
 (952) 448-5300 • Fax (952) 448-2613 • (800) 448-0121

Email: [sales@acousticalsurfaces.com](mailto:sales@acousticalsurfaces.com)

Visit our Website: [www.acousticalsurfaces.com](http://www.acousticalsurfaces.com)

**We Identify and S.T.O.P. Your Noise Problem**

<b>EMERGENCY FIRST AID PROCEDURES</b>	
<b>Eye Contact:</b>	Flush with water for 15 minutes. If irritated, seek medical attention
<b>Skin Contact:</b>	Wash with soap and water. If irritated, seek medical attention.
<b>Inhalation:</b>	Remove to fresh air. Resuscitate if necessary. Get medical attention.
<b>Ingestion:</b>	<b>DO NOT INDUCE VOMITING.</b> Drink two large glasses of water. Get immediate medical attention.
<b>SECTION 6 - CONTROL AND PROTECTIVE MEASURES</b>	
<b>Respiratory Protection (specify type):</b>	If vapor concentration exceeds TLV, use respirator approved by NIOSH in positive pressure mode.
<b>Protective Gloves:</b> Neoprene.	<b>Eye Protection:</b> Safety glasses recommended.
<b>Ventilation Requirements:</b>	Adequate ventilation to keep vapor concentration below TLV.
<b>Other Protective Clothing &amp; Equipment:</b>	None
<b>Hygienic Work Practices:</b>	Wash with soap and water before handling food. Remove contaminated clothing.
<b>SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE</b>	
<b>Steps To Be Taken If Material Is Spilled Or Released:</b>	Absorb with suitable medium. Incinerate or landfill according to local, state or federal regulations. <b>DO NOT FLUSH TO SEWER.</b>
<b>Waste Disposal Methods:</b>	Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.
<b>Precautions To Be Taken In Handling &amp; Storage:</b>	Do not puncture or incinerate containers. Do not store at temperatures above 130°F.
<b>Other Precautions &amp;/or Special Hazards:</b>	<b>KEEP OUT OF REACH OF CHILDREN.</b> Avoid food contamination. Avoid breathing vapors. Remove ignition sources.

*We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.*

**\*\* Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only**

- Soundproofing Products • Sonex™ Ceiling & Wall Panels • Sound Control Curtains • Equipment Enclosures • Acoustical Baffles & Banners • Solid Wood & Veneer Acoustical Ceiling & Wall Systems
- Professional Audio Acoustics • Vibration & Damping Control • Fire Retardant Acoustics • Hearing Protection • Moisture & Impact Resistant Products • Floor Impact Noise Reduction
- Sound Absorbers • Noise Barriers • Fabric Wrapped Wall Panels • Acoustical Foam (Egg Crate) • Acoustical Sealants & Adhesives • Outdoor Noise Control • Assistive Listening Devices
- OSHA, FDA, ADA Compliance • On-Site Acoustical Analysis • Acoustical Design & Consulting • Large Inventory • Fast Shipment • No Project too Large or Small • Major Credit Cards Accepted