



Acoustical Surfaces, Inc.

SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION CONTROL SPECIALISTS

123 Columbia Court North • Suite 201 • Chaska, MN 55318

(952) 448-5300 • Fax (952) 448-2613 • (800) 448-0121

Email: sales@acousticalsurfaces.com

Visit our Website: www.acousticalsurfaces.com

We Identify and S.T.O.P. Your Noise Problems

ACOUSTI-CURTAIN QUOTE/ORDER FORM

Date: _____ Project: _____

CUSTOMER CONTACT INFORMATION

Company: _____ Contact: _____

Address: _____ City: _____

State: _____ Zip: _____ Phone: _____

Fax: _____ E-mail: _____

PRODUCT REQUIREMENTS

Number of Panels/Curtains : _____

1. FABRICS

Drapery Fabric Color – *Please refer to the color chart on our website:*

http://www.acousticalsurfaces.com/acoustical_drapery/acoustical_curtains.htm

A. Face (front): _____

B. Lining (back): Black White

2. DIMENSIONS NOTE: If multiple size curtains are required, please fill out a form for each size.

A. Desired Total Width (side to side): _____

(Standard width is 60". Other width sizes are special order).

B. Desired Total Height (top edge to bottom edge): _____

3. FULLNESS (optional)

The ratio of the total fabric used to the finished width of a drapery. The fuller the drapery, the smaller the spaces between each pleat.

Please specify fullness required: _____

Example: A curtain rod is 71" wide. A curtain for this rod with 1.5 times fullness is figured like this...

(71" x 1.5 = 106.50 total width).

Continued next page...



Acoustical Surfaces, Inc.

SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION CONTROL SPECIALISTS

123 Columbia Court North • Suite 201 • Chaska, MN 55318

(952) 448-5300 • Fax (952) 448-2613 • (800) 448-0121

Email: sales@acousticalsurfaces.com

Visit our Website: www.acousticalsurfaces.com

We Identify and S.T.O.P. Your Noise Problem

4. HANGING METHODS

Header Style (choose 1 of the Header Style's below):

A. Grommet



NOTE: Standard size is 1-3/8" interior diameter.

NOTE: Center of grommet is located 1-5/8" from the top edge of curtain.

Grommet Color: Brass Black Silver

Spacing (required): _____ inches on center (7" to 8" standard).

B. Pleated with Hooks



NOTE: Curtain hooks are installed flush to the top.

Spacing (required): _____ inches on center (6" standard).

C. Tab Top



NOTE: Loops are sewn from the fabric used to create front panel. (See 1A).

Length of Tab Top (measure from top of curtain panel): _____ (4" standard length, 1-1/2" standard width).

Spacing (required): _____ inches on center (6" standard).

D. Rod Pocket with Hook & Loop



(3" standard).

E. Hook & Loop Full Perimeter

5. SEAMS

All seams are vertical unless otherwise specified.

6. CORE

All acoustical drapes will feature 10 oz. yard² wool core material. The core material will stop 2" above the bottom hem.

Continued next page...



Acoustical Surfaces, Inc.

SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION CONTROL SPECIALISTS

123 Columbia Court North • Suite 201 • Chaska, MN 55318

(952) 448-5300 • Fax (952) 448-2613 • (800) 448-0121

Email: sales@acousticalsurfaces.com

Visit our Website: www.acousticalsurfaces.com

We Identify and S.T.O.P. Your Noise Problem

7. COMMENTS

ESTIMATE (office use only)

Curtain Width (final based on options): _____

Curtain Height (final): _____

Cost per Square Foot: _____

Square Feet Required: _____

Curtain Cost: _____

Lead Time: _____

Quoted by: _____

NOTE: Price quotes are good for 30 days from the date of quote.

IMPORTANT: These products are custom made and not returnable.

Please copy form, fill in as much information as you can, and fax or e-mail (sales@acousticalsurfaces.com) your request back. Our sales department will process your request and fax or e-mail you a quote. Please make sure to fill out the contact information completely in case we should have any questions or comments regarding this design.

Thank you

Acoustical Surfaces Inc.

123 Columbia Court North,

Chaska, MN 55318

Phone: 952.448.5300 • Toll-Free: 800.448.0121

Fax: 952.448.2613