



# Acoustical Surfaces, Inc.

**SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION CONTROL SPECIALISTS**

123 Columbia Court North • Suite 201 • Chaska, MN 55318

(952) 448-5300 • Fax (952) 448-2613 • (800) 448-0121

Email: [sales@acousticalsurfaces.com](mailto:sales@acousticalsurfaces.com)

Visit our Website: [www.acousticalsurfaces.com](http://www.acousticalsurfaces.com)

---

---

**We Identify and S.T.O.P. Your Noise Problems**



Part #: ASTSA29

## Physical Properties

**Calculated VOC (less water):**

27 g/L

**Weight/gallon:** 10.13 lbs.

**Flashpoint:** > 200°F.

**Freeze/thaw stability:** Stable

**State:** Medium-viscosity mastic

**Color:** Off White

**Solids:** 69%

**Viscosity:** 82,500 cps

**pH:** 7.5

## Storage life:

More than 1 year in unopened container

## Coverage (maximum):

Approximate length of bead according to bead diameter.

**29 oz. Cartridge**

**1/8" bead:** 355 ft.

**1/4" bead:** 89 ft.

**3/8" bead:** 39 ft.

## GREENchoice™

### Panel & Subfloor Adhesive

- **Environmentally safe – VOC-compliant**
- **Fills gaps and irregularities**
- **Reduces the amount of nailing**
- **Highly water-resistant when dry**
- **Excellent aging qualities**
- **Ideal for use on wet, frozen, treated and engineered lumber**
- **Offers freeze/thaw stability**
- **Cleans easily with water in wet state**
- **Cartridge and carton contain post-consumer recycled material**

GREENchoice Panel & Subfloor Adhesive is a professional-strength formula designed for panel and subfloor installations as well as plywood use. It provides a permanent bond that remains flexible, reduces nailing and helps eliminate squeaky floors.

GREENchoice Panel & Subfloor is a VOC-compliant formula containing no ozone depleting chemicals, making it safer for you and the environment. Unlike solvent-based adhesives, it is nonflammable, emits no harmful fumes and cleans up with water.

## Application Guidelines:

**Application Temperature:** 40°F. to 100°F.

**Service Temperature Range:** 0°F. to 120°F.

**Method of Application:** Cartridge/caulking gun

**Working Time:** Approximately 20 minutes for a 1/4" bead

**Working Surfaces:** Surfaces to be bonded should be clean and free of any material that may deter adhesion. Apply adhesive to only one of the surfaces to be bonded. **NOTE:** For subfloors, nail or screw each sheet as recommended by the American Plywood Association.

**Cleanup:** Clean with water while adhesive is wet. Scrape off dried excess with a putty knife. Remove residue with mineral spirits or equivalent solvent. Follow solvent vendor's precautions when using solvents. **NOTE:** Test solvent on an out-of-the-way area to make sure it will not mar or attack the surface.

## Limitations:

GREENchoice Panel & Subfloor Adhesive is not designed for continuous submersions. For rigid plastics, metal or steel applications, we recommend GREENchoice Premium Polyurethane, please call for details. For best results, store adhesive above 40°F.

## Caution Statement:

**CAUTION: EYE AND SKIN IRRITANT.** Contains ethylene glycol. Do not swallow. Do not allow eye contact or prolonged skin contact. First Aid: If swallowed, do not induce vomiting; contact physician. If eye contact occurs, flush eyes with water for 15 minutes. Wash skin contact areas with soap and water. If irritation from eye or skin contact areas persists, contact physician. For additional information, refer to Material Safety Data Sheet. **KEEP OUT OF THE REACH OF CHILDREN.**