



Acoustical Surfaces, Inc.

SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION CONTROL SPECIALISTS

123 Columbia Court North • Suite 201 • Chaska, MN 55318

(952) 448-5300 • Fax (952) 448-2613 • (800) 448-0121

Email: sales@acousticalsurfaces.com


Visit our Website: www.acousticalsurfaces.com

We Identify and S.T.O.P. Your Noise Problems



PAINTED NUBBY FIBERGLASS Acoustical Ceiling Tile

- **High Performance Acoustics**
- **Lightweight**
- **Durable Woven Facing**
- **Sag-Free**



Panel Texture

MATERIAL: Semirigid fiberglass with a painted woven textured fiberglass facing.

SIZE: 2' x 2', 2' x 4', 4' x 8'.

THICKNESS: 1" or 2".

APPLICATIONS: Ceiling tile applications where high acoustical performance is required.

WEIGHT: 0.5 lb./sq./ft. for 1", 1 lb./sq. ft. for 2".

FLAMESPREAD: Per E-84, 25 f/s, Smoked developed 50.

LIGHT REFLECTANCE: LR-1 (actual .87).

THERMAL RESISTANCE: 1" = R-4.

MAINTENANCE: Can be easily cleaned with soft brush or vacuum.

	Mount	125Hz	250Hz	500Hz	1KHz	2KHz	4KHz	NRC
1"	E	.69	.95	.85	1.06	1.11	1.08	.95