

Acoustical Surfaces, Inc.

SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION CONTROL SPECIALISTS

123 Columbia Court North • Suite 201 • Chaska, MN 55318 (952) 448-5300 • Fax (952) 448-2613 • (800) 448-0121

Email: sales@acousticalsurfaces.com Visit our Website: www.acousticalsurfaces.com

We Identify and S.T.O.P. Your Noise Problems



SONEX Valueline™

Melamine Foam Acoustical Panels

- Fiber Free
- High Performance
- Subtle Texture
- Lightweight

MATERIAL: Melamine Acoustical Foam. PATTERN: Shallow control surface.

FEATURES: High acoustical performance in mid-frequency noise range.

APPLICATIONS: Industrial applications, offices, broadcasting and recording studios for effective reverberation and

reflected noise control.

THICKNESS: 1-1/2", 1-7/8", 2-1/2 SIZES: 2'x4' DENSITY: 0.7 lbs./cub. ft.

STANDARD COLORS: White, Grey, Charcoal. OPTIONAL HPC-COATED COLORS: Black, Light Grey, White, Almond, Medium Grey, Light Blue, Ivory. CUSTOM COLORS: Please contact us to discuss custom color


options.

FLAMMABILITY: ASTM E84, Class A, Natural: F/S 5, S/D 45; Painted: F/S 45, S/D 10.

INSTALLATION: ASI S.T.O.P. Noise Acoustical Adhesive.









Sound Absorption per ASTM C-423-902							
	125Hz	250Hz	500Hz	1KHz	2KHz	4KHz	NRC
11/2 Natural	80.0	0.29	0.73	0.94	0.97	0.89	0.75
11/2 Painted	0.06	0.34	0.79	1.02	1.00	0.98	0.80
17/8 Natural	0.17	0.55	1.07	1.15	1.08	1.10	0.95
17/8 Painted	0.19	0.55	1.17	1.21	1.15	1.13	1.00
21/2 Natural	0.19	0.62	1.15	1.21	1.14	1.20	1.05
21/2 Painted	0.20	0.66	1.20	1.19	1.12	1.12	1.05